

THE HARBOR OF REFUGE

A COMMERCIAL NECESSITY!

Official Report of Cape Foulweather Survey!

EXAMINATION OF CAPE FOULWEATHER HARBOR, OREGON.

Reports of Col. Wilson and R. A. Habersham.

UNITED STATES ENGINEER OFFICE, Portland, Or., Sept. 23, 1878.

GENERAL: I have the honor to transmit herewith a chart of Cape Foulweather Harbor, Oregon, together with the report of Mr. R. A. Habersham, assistant engineer, and to submit the following report of an examination and survey made under my direction in accordance with the act of Congress, approved June 18, 1878.

OBJECT OF EXAMINATION. The object of the examination and survey of this harbor was to ascertain its adaptability as a harbor of refuge.

Early in August I organized a party for this work and placed it in charge of Mr. R. A. Habersham, assistant engineer, with orders to proceed to Cape Foulweather and make the necessary surveys to carry out the law. This party proceeded to Corvallis, Oregon, via the Willamette river; thence by wagons across the Coast Range of mountains to Newport, on Yaquina Bay, and thence to Cape Foulweather, where they camped until the survey was completed. On Sept. 8th, I visited Cape Foulweather and made a general examination of the locality.

DESCRIPTION OF THE HARBORS. Cape Foulweather is situated on the western coast of Oregon, in latitude 44 degrees 43 minutes north, longitude 124 degrees 05 minutes west, and forms a headland boldly jutting out about three-fourths of a mile into the sea from the low beach with high mountains in rear of it.

It is a mass of black basalt rising to a height of from 80 to 100 feet above the sea, the base honeycombed with caves formed by the action of the waves. The cape, by its position, forms bays on the north and south, the one fronting northwest and the other south and southwest. On the north shore line is crescent shaped, the outer extremity pointing north, a reef making out from it in a direction north-northeast a distance of about 5,000 feet, terminating at a lone rock about 1,800 feet from the beach. The depths on this reef vary from 10 to 30 feet, except for a distance of about 1,200 feet near the cape, where there is a channel of that width with a depth of from 30 to 40 feet. The lone rock referred to at the north end of the reef seems to be connected with a rocky point opposite on shore by a well-marked reef, upon which there is a depth of four fathoms.

The north bay is inclosed, there fore, on the east by the mainland, on the south by the cape, and on the west by the long reef. It is nearly a mile long, and about 1,700 feet wide between the three-fathom curve and the reef. It contains about 200 acres, with a depth of from 3 to 8 fathoms, and a sandy bottom. As far as could be judged, there is good holding ground for anchoring vessels, although I understand that no vessel has ever entered.

This south bay is formed by the main shore and the cape, and is protected on the east, north and northwest. It is open and exposed to the terrible southern gales, from which it is most desired to find shelter. The bottom is sandy, the depth gradually increasing from near the shore, where it is 3 fathoms, to 20 fathoms 2 miles off shore. The general depth, on a line drawn south from the cape, is from 4 to 6 fathoms.

TIDES, FOGS, &c. The spring tides rise and fall about 9 feet. Dense fogs overhang the cape from time to time during the year, particularly during the month of July.

THE HARBOR OF REFUGE. About 3 1/2 miles south of Cape Foulweather is Yaquina Bay, the mouth of Yaquina river. A railroad is projected to connect this bay with the Willamette river. It is anticipated that when this is completed a large amount of grain and other produce now finding its market via the Willamette and Columbia rivers will seek an outlet via the Yaquina Bay.

About three quarters of a mile off the entrance to this bay a dangerous reef of rocks, extending in a north and south direction, with many narrow and dangerous channels across it, is reported by the Coast Survey, and laid down on their charts. I am informed that the residents in the vicinity presumed that a reef extended from Yaquina Head toward the cape, and inclosed an area of about 5,000 acres, the ridge being, they thought, well defined, and that upon it a breakwater could be constructed which would form a fine harbor of refuge.

As far as I could learn, the object of this survey was to locate a breakwater upon this supposed reef for a harbor of refuge. The chart of the United States Coast survey shows no such reef and

the very careful examination of Assistant Engineer Habersham reports four knobs of rock apparently much higher than the rest of the bottom from 12 to 30 feet under low water level situated in a curved line in the direction above indicated, but distant from each other from one-fourth to one-half a mile and with from 6 to 8 fathoms of water between them. On these during low tide and heavy weather the sea breaks constantly.

The chart transmitted herewith shows a breakwater projected on this line, starting from near Yaquina Head and running west, then curving to the north, and terminating about a mile and a half from the cape. Such a harbor would present a large area amply protected from southwest gales, with a depth of from 3 to 8 fathoms. The cape proper already presents a good protection from gales from the north and northwest. This breakwater would be about 9,900 feet long, and constructed upon the plan adopted by the board of engineers for the Pacific coast. It is described in their report of February 14, 1877, as follows:

"We propose to build the base of any breakwater up to the height of 15 feet below the level of low water of small tides; that is to say, of such stone as any quarry will furnish, and while quarrying out this great mass to lay away all large stones of 5, 10 or 20 tons for the construction of that portion of the breakwater from 15 feet up to low water. Upon this foundation we propose to build a masonry wall faced with granite 25 feet wide and 20 feet high, including foundation, protecting the seaward side by blocks of artificial stone (if natural cannot be obtained) of large size (20 or 30 tons each) and thoroughly paving the harbor side with large blocks of granite to receive without displacement the water that will be thrown over the wall in great storms."

The cost of such a breakwater is estimated by Assistant Engineer Habersham to be as follows:

Ninety-nine hundred feet, at \$1,052.57 per foot... \$10,420,443 00 Contingencies, 10 per cent... 1,042,044 00 Total... 11,462,487 00

It is highly probable that for present purposes a breakwater would be sufficient starting from Yaquina Head, running on the line projected, terminating in 4 1/2 fathoms of water and having a length of 4,900 feet; such a work would cost as follows:

Forty-nine hundred feet, at \$851.57 per foot... \$4,187,333 00 Contingencies, 10 per cent... 418,733 00 Total... 4,606,132 00

Such a breakwater would present an area of 200 acres protected from gales from the south and southwest. The difficulty to be contended with in using this harbor would be that sailing vessels entering during a southwest gale would be obliged in rounding the outer end to face the wind.

Assistant Engineer Habersham made a careful examination of the bay north of the cape; no survey has ever before been made, it is believed, of this bay, and as far as he could learn his boat was the first that ever entered it. He reports that it is a natural harbor of considerable extent without further improvement, and that he was informed that during southwest gales quite an area inside is comparatively smooth. Several of the seamen who were employed as boatmen on the survey, who had sailed for a number of years between San Francisco and Puget Sound, and claimed to be familiar with the coast, said that if buoys were placed to mark the entrance, vessels could now enter for shelter from southwest gales. From the examination made under my direction by Assistant Engineer Habersham, and from his report and my own observation, I think a better harbor can be made north of the cape than south of it, by constructing a breakwater running in a northwest direction just inside the reef running out from the cape; such a breakwater would be about 600 feet long and would contain within it an available anchorage of from 50 to 100 acres with a depth of from 3 to 8 fathoms.

The plan for such a work would be similar to that already described, and the cost is estimated by Mr. Habersham at \$656,251.

The harbor could be greatly increased in size by constructing a breakwater on the reef parallel to the shore already described. This north harbor, with the 600-foot breakwater, would only be available in south and southwest gales; but during heavy weather from the northwest vessels could anchor on the other side of the cape.

Attention is respectfully invited to the interesting report of Assistant Engineer Habersham transmitted herewith. In making the examination there were numerous minor difficulties to overcome, and Mr. Habersham deserves credit for the efficient manner in which he carried out my instructions.

Cape Foulweather is in the collection district of Southern Oregon. The nearest port of entry is at Newport, Yaquina Bay; no revenue was collected during the last fiscal year; there were no foreign imports or exports; about 600 tons of assorted merchandise are brought in annually by coast-wise vessels which carry away lumber and oysters; two sailing vessels of about 100 tons burden each, with a draught of 9 feet, are running between San Francisco and Yaquina Bay.

There is a first order light house on the cape, visible 19 miles. The nearest works of defense are at the mouth of the Columbia river.

The value of the commerce to be benefited by this work would run up into millions, as the benefit would be felt by every vessel navigating the

Pacific Ocean between San Francisco and the straits of Fuca. For the necessity for a harbor of refuge on this Northern Pacific Coast, I respectfully call attention to the interesting and elaborate report of the board of engineers for the Pacific coast dated February 14, 1877.

I am, General, very respectfully, your obedient servant, JOHN M. WILSON, Maj. of Eng., Brev. Col. U. S. A., Brig. Gen. A. A. HUMPHREYS, Chief of Eng. U. S. A.

REPORT OF MR. ROBERT A. HABERSHAM, ASSISTANT ENGINEER, UNITED STATES ENGINEER OFFICE, Portland, Or., Sept. 16, 1878.

COLONEL: I have the honor to submit the following report of a survey "at Cape Foulweather, to ascertain its adaptability as a harbor of refuge," with a general plan of improvement, and an approximate estimate of its cost, made in pursuance of your instructions dated August 8, of the present year.

This work was performed between the 9th and 23d of the same month. To save repetition, I will here state that all depths given refer, unless otherwise specified, to the lowest of mean low tides, as nearly as could be determined from the tide tables for the Pacific coast, published in San Francisco, and from information furnished by residents of the locality.

No extreme tides occurred during the progress of the survey, not even at full moon, an unusual circumstance.

TOPOGRAPHY AND HYDROGRAPHY AT CAPE FOULWEATHER AND ITS VICINITY. From Yaquina Head, which marks the north side of the entrance to Yaquina river, the shore line runs a little to the east of north for 4 miles, to the end of South Foulweather Beach; thence westward for three-fourths of a mile to the southwest elbow of the cape, where it begins to curve northward and eastward until it reaches the extreme point of Cape Foulweather, which points north; thence southward, curving round to east, to the point where the cape joins the mainland again; thence north for about 7 miles to a point known as Old Cape Foulweather.

The shore line of Cape Foulweather proper describes the figure of a half crescent, the curved tip pointing north. From this point a reef makes out in nearly a direct line, course north northeast, for 5,025 feet, terminating in a bare rock, which, for convenience, I have called Round Rock, distant 1,800 feet from the low tide line on the north beach, and immediately opposite Rocky Point, a vertical cliff formed of rock of the same character, of which it was formerly a portion, as the soundings show a well marked ridge connecting them about four fathoms under water.

The depths on this long reef, which is nearly flat on its crest, vary from 10 to 30 feet from Round Rock to within 1,200 feet of the cape, where a depression occurs which shows from 30 to 40 feet; the center being the deepest. The north side of this gap is marked by a rock on which the swell breaks constantly, and which is said to be bare at extreme low tide.

It is seen that the cape forms two bays, one fronting northwest, the other south and southwest. The north bay, the outlines of which have just been given, is inclosed on the east by the mainland; on the south and southwest by the cape; on the west by the long reef which connects Round Rock with Rocky Point. It is nearly one mile in length and one-third of a mile across, the width being measured from the curve of 18 feet depth to the west reef, and contains about 200 acres. The bottom is sandy, generally smooth, forming good holding ground as far as can be judged, no vessel or craft of any kind having up to this time entered here that I can learn. The depths vary from 3 to 8 fathoms.

The south bay, so called, is open to the south and west. It is bounded on the north by the cape and on the east by the mainland. The bottom is sandy, sloping seaward, the depth increasing uniformly from near the beach, where it is 18 feet to 20 fathoms at a distance of 2 miles from the shore. The general depth on a line drawn south from the cape is from 4 to 6 fathoms. It is rather a roadstead than a bay; and while it is easy of access from the ocean in any direction, is sheltered only from north and east winds, which are never violent.

From Yaquina Head to the north end of Foulweather Beach the shore presents a slope of from 50 degrees to 80 degrees, tolerably uniform in direction generally, but much broken by sharp points and ravines and small valleys. The face of the cliff shows soft sandstone overlying at greater or less depths a bed of marl filled with fossil shells. Numerous small veins of water trickle down the face of the sandstone, softening it and contributing to the destructive action of the weather, while the marl underneath is also wearing away under the heavy blows of the surf.

Between Yaquina Head and the cape four streams large enough to furnish good water power, flowing through small valleys more or less heavily timbered, enter the ocean. Except in these valleys the vegetation, although luxuriant, is of small growth, and consists of salal, whorledeberry, fern and scattering spruce ferns. The beach is from 300 to 500 feet wide, generally sandy, but the frequent occurrence of rocks above the surface show that the sand has little depth. The shore north of the cape is of the same general character.

Cape Foulweather is a promontory, covered with a thick carpet of grass and fern, making out from the continent, its crest line running from east to west, at right angles to the general

course of the shore line, crossing two conical summits respectively 400 and 350 feet high, descending the latter at a slope of about 30 degrees and terminating in a flat point 80 feet above mean sea level, on which the lighthouse stands. The neck where the promontory joins the continent is 2,300 feet across between low water levels and about 200 feet above sea level at its highest point. The promontory is a mass of dense, hard, black basalt, which seems to have been forced like a wedge into a cleft in the sandstone. It rises vertically from the sea to a height of from 80 to 150 feet, in many places, overhanging the water; its face hollowed out into caverns and studded with fissures, with the sharp projections of fantastic shape; the whole crumbling away slowly from the effects of the winter fogs and rains. The base of the cliff is honey-combed with caves, some of which might well be called tunnels, as they extend a long distance into the rock. One is said to penetrate 80 feet in a direct line from the face. It was not possible to verify this statement by measurement, as the surf was washing in and out of the cave with great force, but it is probably not far from the truth. The west end of the cape is surrounded by a number of pinacles of rock rising vertically to a height of from 40 to 80 feet out of the water. Seen from a boat at a short distance, this black, jagged mass towering into the air, with the surf lashing its base with a noise like thunder, the scene excels in grandeur, the sight of Devil's Canyon and Cape Horn, on the Central Pacific Railroad; but it must be a sight of terror to the unfortunate mariner who should see it as a lee coast during the southwest gale.

From November to April the prevailing winds are southerly. Sometimes strong west winds occur, changing round to northwest, breaking into heavy squalls, accompanied by rain, hail, thunder, and lightning. This is generally from February to April. The gales which are principally dreaded by mariners come from the southwest. These are sometimes so strong that a man cannot keep his feet, and pebbles as large as hazelnuts are caught up from the beach and dashed against the light tower, to a height of more than 100 feet. These gales reach a velocity of 60 miles per hour. Fogs so dense that the shore is not visible from a distance of 500 feet out at sea occur at all seasons of the year. Rain during the winter is not so frequent as in the Willamette Valley, but heavier; snow is of rare occurrence, always light, and soon melts.

For the information contained in this paragraph I am indebted to Captain S. P. Wass, custodian of the light house at Cape Foulweather.

TIDES. The spring tides, with the ocean in its normal condition, rise and fall 9 feet. During strong west winds the high tides have reached a height of 12 feet above mean low water mark. The influence of ordinary high tides extends to Pioneer, 30 miles above the mouth of the Yaquina, the tide rising and falling from 4 to 6 feet.

LOCATION FOR A HARBOR OF REFUGE. It has generally been believed by the residents of the country around Yaquina Bay that a reef from 3 to 5 fathoms under water extends in a curved line from Yaquina Head toward Cape Foulweather, terminating about one and a half miles south of the cape, inclosing a basin having a smooth, sandy bottom, which covers an area of nearly 1,000 acres, and that a breakwater built along the crest of the supposed reef would convert the basin into a harbor of shelter for vessels in distress as well as a port of entry.

It was for the purpose of ascertaining the feasibility of this project that a survey was requested by those interested, among whom may be included all of the people of that section of Oregon whose nearest outlet to the ocean lies through the valley of the Yaquina river. The chart of the United States Coast Survey in this locality and my soundings over the same ground show that no such reef exists. There are 4 knobs of sandstone, harder than the rest of the bottom, from 12 to 30 feet under low water level, situated in a curved line in the direction above indicated, but distant from each other from one-fourth to one-half a mile, and with from 30 to 50 feet of water between them. On these, during low tides and heavy swells, the sea breaks constantly, suggesting the presence of a continuous reef.

The length of breakwater which this project contemplates would be 9,900 feet, with an average depth of 20 feet below low tide level. Its cost per linear foot, on the general plan recommended by the board of engineers, Pacific coast, would be as follows:

Asphalt masonry, 21.67 cubic yards, at \$18... \$410 00 Rubble masonry, 14.08 cubic yards, at \$29... 408 32 Small rough rubble, 73.00 cubic yards at \$3... 219 00 Large rough rubble, 59.25 cubic yards at \$5... 296 25 Per linear foot... \$1,052 57

Nine thousand linear feet, at \$1,052.57... \$10,420,443 00 Add for contingencies 10 per cent... 1,042,044 30 Total... \$11,462,487 30

The estimate for rough rubble may appear excessive, but the stone would have to be brought from Cape Foulweather, the nearest point where hard rock is found, and where, owing to the prevalence of heavy seas, the loading of barges would be expensive and dangerous, often impossible, necessitating the suspension of the work until the recurrence of smoother

weather should allow the boats to approach the quays with safety. There is no question that such a work, if carried out, would greatly benefit navigation by affording shelter from southwest gales. Some such protection is absolutely required. But a better harbor, at much less cost, would be secured by building a breakwater from the extreme point of Cape Foulweather northward, inside of the reef above described, for a distance of 600 feet. This would inclose an area of about 100 acres, under the lee of the cape, with good anchorage, in from 4 to 8 fathoms of water, having a free entrance from the west 1,200 feet wide. Such a harbor would satisfy the present necessities, not only as a refuge but also as a port of entry, Yaquina Bay being accessible only to light-draught coasting vessels; and it might be enlarged at any future time, if desired, by extending the breakwater along the reef.

The cost per linear foot of a breakwater here on the plan recommended, would be as nearly as can be estimated from the data obtained, as follows, its dimensions being: Length 600 feet, average depth below low tide 31 feet.

Asphalt masonry... \$410 00 Rubble masonry... 126 72 Small rough rubble, 110 cubic yards, at \$2... 220 00 Large rough rubble, 59.25 cubic yards, at \$4... 237 00 Per linear foot... \$994 32

Making for its length of 600 feet, \$596,592 00 Add for contingencies 10 per cent, \$59,659 20 Total... \$656,251 20

Here the stone could be obtained from the shore end of the wall and hauled in cars along the top, extending the track as the work progressed, making the cost of transportation less than in the south bay. The above estimates are in gold coin. The hydrographic work of the Coast Survey in this vicinity terminates at the extremity of Cape Foulweather. No survey had ever been made of this bay, and so far as I could learn, my boat was the first that had ever entered it. It is a natural harbor of considerable extent, even without improvement. I am informed that during southwest gales the whole of the area inside of the reef is comparatively smooth, and the southeast portion quite so. Several of the seamen employed as boatmen on this survey, who had sailed for a number of years between San Francisco and Puget Sound, and claimed to be familiar with the coast and its climate, said that if two buoys were placed to mark the entrance, and the fact published for the information of mariners, vessels of any draught could enter here, not only for shelter, but for purposes of commerce. If this opinion be correct—and there seems to be no reason to the contrary—the circumstance is of interest in connection with the fact that a narrow gauge railway is now under construction from Corvallis, on the Willamette to Yaquina Bay.

Last winter there were a number of vessels in distress off Cape Foulweather at different times, and one that I am aware of was lost, with all on board. In describing this bay I omitted to mention that there is a rock on which the swell breaks during westerly and northerly weather. It is small, and lies about 500 feet from the mainland, nearly opposite the entrance. It is not in the way of vessels anchoring.

Learning that a cove, with good anchorage, existed about ten miles north of the cape, and wishing to get all information possible on the subject of a refuge, I went there by sea, two members of my party being familiar with the spot. I found it to be an indentation in the rocky coast, three-fourths of a mile long and about 1,000 feet wide; its longer diameter parallel to the general direction of the coast line, with from 6 to 10 fathoms depth, well sheltered from north wind, but open to the west and southwest. This place is called Wrecker's Cove, the name having been given by men who saved, or rather, collected, some fragments of the schooner, Uncle Sam, lost a mile north of the cove about two years since. Respectfully submitted, ROBERT A. HABERSHAM, Assistant Engineer, COLONEL JOHN M. WILSON, Maj. Corps Eng's, U. S. A.

A Bridgeport artist has painted a very natural fence, but the critics will picket all to pieces.

Church Directory. Catholic Church: Services on the last Sabbath of each month. Mass commences at 10:30 A. M. Rev. VAN LEE, Pastor. M. E. Church South: Preaching morning and evening on the 1st, 3rd and 4th Sabbath of each month, at 11 and 7:30 respectively. Sabbath school at 9:30 every Sabbath. JOSEPH EASTAY, Pastor. Evangelical Church: Services at 7 P. M. on the 1st and 3rd Sabbath and at 11 A. M. and 7 P. M. on the 4th Sabbath of each month. Sabbath school at 9:30 P. M. Prayer meeting Wednesday evening of each week, at 7 P. M. W. G. HANSEN, Pastor. Presbyterian Church: There will be preaching morning and evening at 11 and 7 o'clock, respectively. Sabbath school immediately after the morning service. H. F. HANSEN, Pastor. M. E. Church: Services the 2nd and 4th Sabbath of each month, at 11 A. M. and 7 P. M. Prayer meeting, Tuesday evening at 7 P. M. Services at Grange Hall, four miles west of Corvallis, the 1st and 3rd Sabbath of each month, at 11 A. M. and 7 P. M. W. G. HANSEN, Pastor. Episcopal Church: The services for the month of Oct. will be as follows: the 5th and 12th at 7:30 P. M., Oct. 19th and 26th at 11 A. M., with Holy Communion. Sunday school every Sunday, between the hours of 3 and 4 P. M. Rev. L. STEVENS.

CORVALLIS LODGE No. 14, F. & A. M. holds stated Communications on Wednesday or on preceding each full moon. Brethren in good standing are cordially invited to attend. By order of W. M. HARNUM LODGE No. 7, I. O. O. F., meets on Tuesday evening of each week in their Hall, in Fisher's Brick, second story. Members of the Order held in good standing, are invited to attend. By order of W. G. Crystal Lake Cemetery. Persons desiring to obtain Lots, can obtain all the necessary information, by applying to E. HOLEMAN, Com.

RUPTURE! ANOTHER WONDERFUL CURE - EFFECTED BY - CALIFORNIA ELASTIC TRUSS!

SUBSCRIBE FOR THE WEEKLY Corvallis Gazette, FOR 1879! VOL. SIXTEEN.

OFFICIAL PAPER FOR BENTON COUNTY! WILLAMETTE VALLEY.

THE GAZETTE! IS A LIVE LOCAL PAPER, Has a Large, and Constantly Increasing circulation, and is one of the BEST ADVERTISING MEDIUMS in the State, being published in the heart of the WILLAMETTE VALLEY.

\$2 50 Per Annum, INVARIABLY IN ADVANCE.

Advertisements inserted at Reasonable Rates.

All kinds Plain and Ornamental Printing executed with neatness and dispatch. Justices' Blanks constantly on hand.

W. B. CARTER, Proprietor and Publisher, Corvallis, Oregon.

RUPTURE! ANOTHER WONDERFUL CURE - EFFECTED BY - CALIFORNIA ELASTIC TRUSS!

California Elastic Truss Co. After practicing medicine many years in this city, during which time I have had an extensive experience in the application of all kinds of Trusses, I can and do recommend yours as the best in every respect. It is as near perfection as modern science can make it. It has many advantages over other Trusses, which inflict great injury on the hips and spine, bringing on other diseases, such as sciatica, morbid affections of the kidneys and bladder, in the lower limbs, all of which are avoided by wearing the California Elastic Truss. It is not only a perfect retainer, combining ease and comfort, but the pressure can be changed to any degree. It also remains in its proper place at all times, regardless of the motions of the body, and is worn night and day with perfect ease. It is superior to all other Elastic Trusses now in the market, while it combines the best of all 1st class Trusses, which will cure all the most essential to comfort and durability, and is unequalled in lightness, elasticity, natural action, and artistic finish. Many of my patients who are afflicted with hernia are wearing them, and all shall in the future, for I think the great use which will be made of these purely scientific appliances are made efficacious, is truly remarkable. I can change to any parties to me on the subject of their merits. I remain truly yours, L. DEXTER LYFORD, M. D., Physician and Surgeon, 600 Sacramento street, San Francisco.

It is constructed on scientific principles and sells on its own merits. If you wear any other material, don't forget the name and number. Trusses forwarded to all parts of the United States at our expense, on receipt of any parties to me on the subject of their merits. I remain truly yours, L. DEXTER LYFORD, M. D., Physician and Surgeon, 600 Sacramento street, San Francisco.

Send for Illustrated Catalogue and Price List, Giving full information and rules for Measuring. CALIFORNIA ELASTIC TRUSS COMPANY, 720 Market Street, S. F. 1535y1.

CONSUMPTION Positively Cured. ALL SUFFERERS FROM THIS DISEASE THAT are anxious to be cured should try Dr. Kiser's Celebrated Consumptive Powders. These Powders are the only preparation known by its name ever manufactured, don't forget the name and number. Trusses forwarded to all parts of the United States at our expense, on receipt of any parties to me on the subject of their merits. I remain truly yours, L. DEXTER LYFORD, M. D., Physician and Surgeon, 600 Sacramento street, San Francisco.

Send for Illustrated Catalogue and Price List, Giving full information and rules for Measuring. CALIFORNIA ELASTIC TRUSS COMPANY, 720 Market Street, S. F. 1535y1.

THE Scientific American. THIRTY-FOURTH YEAR. THE MOST POPULAR SCIENTIFIC PAPER IN THE WORLD. Only \$3.20 a Year, including Postage. Weekly, 52 Numbers a Year. 4,000 page.

THE SCIENTIFIC AMERICAN is a large First-Class Weekly Newspaper, published in the most beautiful style, profusely illustrated with splendid engravings, representing the progress of the human mind in the Arts and Sciences, including New and Interesting Facts in Agriculture, Horticulture, the Home, Health, Medical Progress, Social Science, Natural History, Geology, Astronomy, the most valuable practical papers, by eminent writers in all departments of Science, will be found in the Scientific American. Terms, \$3.20 per year, \$2.00 half year, which includes postage. Discount to Agents. Single copies, ten cents. Sold at Newsdealers. Remit by postal order to MUNN & CO., Publishers, 27 Park Row, New York.

Patents. In connection with the SCIENTIFIC AMERICAN, Messrs. MUNN & CO. are Solicitors of American and Foreign Patents, have had 34 years' experience, and now have the largest establishment in the world. Patents are obtained on the most liberal and special terms in the Scientific American of all Inventions patented through this Agency, with the most rapid and efficient of the Patent Office. By the immense circulation thus given, public attention is directed to the merits of the new patent, sales or introduction often easily effected. Any person who has made a new discovery on invention, can ascertain, free of charge, whether a patent can be obtained, by writing to the undersigned. We also send free our Handbook about the Patent Laws, Patents, Carrots, Trade-Marks, their costs, and how procured, with hints for procuring advance on inventions. Address for the paper, or concerning Patents, MUNN & CO., 27 Park Row, New York. Branch Office, Cor. F & 7th Sts., Washington, D. C. 15-467f.

CORVALLIS LIVERY, FEED AND SALE STABLE, MAIN STREET, CORVALLIS, OREGON. AND SOL. KING, - Proprietor.

OWING BOTH BARS I AM PREPARED TO offer superior accommodations in the Livery line. Always ready for a drive.

GOOD TEAMS At Low Rates. My Stable, are first-class in every respect, and competent and obliging hostlers always ready to serve the public. REASONABLE CHARGES FOR HIRE. Particular Attention Paid to Boarding Horses. ELEGANT HEARSE, CARRIAGES AND HACKS FOR FUNERALS. Corvallis, Jan. 8, 1879. 163y1.